



QSW-1208-8C	
Management Type	Unmanaged
Number of Ports	12
10GbE SFP+	4
	10G/1G
10GbE SFP+/RJ45 Combo Ports	8
	Note: The 10GbE SFP+ ports are backward compatible with 1GbE SFP; the RJ45 (copper) combo port supports up to five speeds (10G/5G/2.5G/1G/100M).
Power Supply Description	Internal Open Frame
Max. Power Consumption	50W
Input Power Type	AC
Input Voltage Range	100-240VAC, 50/60 Hz
MAC Address Table	32K
Total Non-Blocking Throughput	120Gbps
Switching Capacity	240Gbps
Fan	System: 2 x 4 cm (12V DC)
Supported Standards	IEEE 802.3ab 1000BASE-T Gigabit Ethernet IEEE 802.3bz 2.5G/5G BASE-T Multi-Gig Ethernet IEEE 802.3an 10GBASE-T 10G Ethernet IEEE 802.3ae 10GBASE-SR IEEE 802.3ae 10GBASE-LR IEEE 802.3x Full-duplex flow control
Form Factor	Desktop
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Dimensions (HxWxD)	43 × 285 × 233 mm
Weight (Net)	2.15 kg

Weight (Gross)	2.2 kg
Operating Temperature	0°C to 40°C (32°F to 104°F)
Relative Humidity	10% to 85% RH non-condensing
Certifications	CE, FCC, VCCI, BSMI RCM
Electromagnetic Compliance	CLASS A, UL62368
Jumbo Frames	9k
Warranty	2 Years

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.