



| QSW-3205-5T                                        |                                                                                                                                                                                             |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Management Type                                    | Unmanaged                                                                                                                                                                                   |
| Number of Ports                                    | 5                                                                                                                                                                                           |
| 10GbE BASE-T (RJ45)                                | 5                                                                                                                                                                                           |
|                                                    | 10G/5G/2.5G/1G/100M                                                                                                                                                                         |
| Power Supply Description                           | Adapter                                                                                                                                                                                     |
| Max. Power Consumption                             | 36W                                                                                                                                                                                         |
| Input Power Type                                   | DC                                                                                                                                                                                          |
| Input Voltage Range                                | 12V/3A                                                                                                                                                                                      |
| MAC Address Table                                  | 16K                                                                                                                                                                                         |
| Total Non-Blocking Throughput                      | 50Gbps                                                                                                                                                                                      |
| Switching Capacity                                 | 100Gbps                                                                                                                                                                                     |
| Energy Efficient Ethernet (IEEE 802.3az complaint) | Yes                                                                                                                                                                                         |
| Fanless                                            | Yes                                                                                                                                                                                         |
| Supported Standards                                | IEEE 802.3 Ethernet<br>IEEE 802.3u 100BASE-T<br>IEEE 802.3ab 1000BASE-T<br>IEEE 802.3bz 2.5G/5GBase-T<br>IEEE 802.3an 10GBASE-T<br>IEEE 802.3az EEE<br>IEEE 802.3x Full-Duplex Flow Control |
| Form Factor                                        | Desktop                                                                                                                                                                                     |
| LED Indicators                                     | Per Port: Speed/Link/Activity<br>Per System: Power/Status/Loop                                                                                                                              |
| Dimensions (HxWxD)                                 | 34 x 180 x 145 mm                                                                                                                                                                           |
| Weight (Net)                                       | 0.96 kg                                                                                                                                                                                     |
| Weight (Gross)                                     | 1.2 kg                                                                                                                                                                                      |

|                            |                                             |
|----------------------------|---------------------------------------------|
| Operating Temperature      | 0°C to 40°C (32°F to 104°F)                 |
| Relative Humidity          | 10~95% Non-condensing                       |
| Certifications             | CE, UKCA, FCC, IC, VCCI, RCM, BSMI, LVD, KC |
| Electromagnetic Compliance | CLASS A                                     |
| Jumbo Frames               | 12K                                         |
| Warranty                   | 2 Years                                     |

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.